

Art. no. .11.303.105

Welding Automat, steerable

KA 1-UP

6Steerable welding automat for SAW with wires up to 5 mm diameter for inside welding of tubes and tanks (butt and fillet seams).

In connection with Kjellberg Welding Rectifiers various technological solutions for an effective application in different industries are given.

Advantages for Application:

- Mobile, self-propelled welding automate, which easily can be moved to any working place.
- Flexible application because of modular principle.
- Pre-set controls for welding current, arc voltage and travel speed in connection with Kjellberg power sources.
- Start and stop circuit for optimising the welding process.
- Start and crater filler parameters separate to adjust.
- The tractor runs directly on the workpiece.
- Easy adaptation to other welding technologies.
- Versatile welding head positioning by steering unit ensures optimal seam geometry.
- Inside welding of tubes and boilers with min. 1,500 mm diameter.



Main Features:

- Tachgenerator controlled tractor with all-wheel drive; 160mm diameter wheels, with rubber rims (optional); dust protected manual drive coupling; track gauge 395 mm.
- Wire feed gear with two-roller drive for wire diameters 2.5 to 5.0 mm for SAW single-wire welding
- Cross slides for manual head adjustment of max. 100 mm in horizontal and vertical direction.
- Manual cross (electrically on request) slide with steering unit
- Controls with parameter pre-setting for welding current, arc voltage and travel speed in the first service level and start and stop parameters in the second service level.
- Side rollers to guide the tractor along bars, profiles, etc.
- High stability by double steering wheels.
- Reel holder.
- Flux hopper with 10 l capacity, with sight glass, prepared for connection of a pneumatic flux recovery (optional).
- Two local lightings for dark work stations.
- Laser pointer for visual wire-to-seam control.
- Water-level for optimum positioning in the tank.

Technical data:

Application		SAW single-wire
Welding current	(A)	1400
Control voltage	(V/Hz)	42 AC / 50
Travel gauge	(mm)	395
Wire diameter	(mm)	2,5 – 5,0
Wire feed speed	(m/min)	0,1 – 6,1
Travel speed	(m/min)	0,1 – 2.0
Cross / height adjustment	(mm)	100 / 100
Column swivel range	(degree)	360
Welding head inclination	(degree)	45 (both sides)
Tube inside welding from diameter	(mm)	1500
Weight automat	(kg)	61
Wire reel capacity	(kg)	30
Dimensions automat L x W x H	(mm)	≈ 1050 x 600 x ≈ 900

- EN 60974-1, VDE 0544, VBG 15 (UVV 26.0) and CE sign, produced according to DIN EN ISO 9001.
- S sign, applicable to welding jobs at work places with increased electrical endangerment.

We reserve the rights for technical amendments. This is based on our General Terms of Production and Delivery. Edition 12/09

Kjellberg Finsterwalde Schweißtechnik- und Verschleißschutzsysteme GmbH, NL Finsterwalde

DE - 03238 Finsterwalde • Leipziger Str. 66-68 • Tel.: +49 3531 500 -319 • Fax: +49 3531-357 E-Mail: • schweissen@kjellberg.de
• Hauptsitz: 58453 Witten • HRB 11721 AG Bochum • Geschäftsführer: Heiko Schröder